

RNAV 1 required, EXC DOBAK SID.

TRANSITION ALTITUDE: 3000 AMSL
MAX 250 KIAS below FL 100 unless otherwise instructed.
Initial turn: climb to 500 FT AMSL before turning due to obstacles.
NOTES:
1. For continuation of the routes see AD 2.EHGG-SID-OVERVIEW.
2. For crossing conditions on ATS routes see AD 2.22 paragraph 1.4.3. (due to MIL areas or crossing traffic)

SPIJKERBOOR 2D
ENKOS 2D

TEMLU 3D

EELDE / EEL
112.400 / CH71X
530951.0N 006400.3E
0

OLWOF 1D


DOBAK 3D

ROLDU 2D

PAMPUS 3D

NOVEN 2D

NAPRO 2D
See note
RUMER 3D
SONEB 3D
TEBRO 3D



THR 23	530729.8N	0063525.0E
GG521	524702.4N	0061524.0E
GG522	522253.7N	0061506.3E
GG527	525730.6N	0062638.1E
GG528	525210.4N	0060546.5E
GG529	530512.5N	0063034.5E
GG530	530436.8N	0062420.1E
GG532	530243.4N	0062749.0E
GG533	525935.2N	0064005.0E
GG535	530454.7N	0064645.8E
GG536	531110.8N	0065440.3E

TWR	118.705	Eelde Tower	Primary
	121.705	Eelde Delivery	
APP	120.305	Eelde Approach	Primary
	119.705	Eelde Approach	
ATIS	121.500	General Emergency	
	133.555	Eelde Information	

