



<p>For description VFR - procedures see EHRD AD 2.22.</p> <p> ⋯ Area to be avoided → Outbound → Inbound </p>		<p>SCALE 1 : 50 000</p> <p>M 1000 500 0 1000</p> <p>FT 2000 0 2000 4000</p> <p>DIRECTIONS ARE MAGNETIC DISTANCES IN NM ALTITUDES AND ELEVATIONS IN FEET AMSL HIGHEST KNOWN ELEVATION ON THIS CHART: 613</p>		<table border="1"> <tr> <td>TWR</td> <td>118.205</td> <td>Rotterdam Tower</td> </tr> <tr> <td></td> <td>119.705</td> <td>O/R</td> </tr> <tr> <td></td> <td>122.180</td> <td>Rotterdam Delivery Start-up control & clearance delivery</td> </tr> <tr> <td>APP</td> <td>122.990</td> <td>Rotterdam Approach</td> </tr> <tr> <td>ATIS</td> <td>128.565</td> <td>Rotterdam Info</td> </tr> </table>		TWR	118.205	Rotterdam Tower		119.705	O/R		122.180	Rotterdam Delivery Start-up control & clearance delivery	APP	122.990	Rotterdam Approach	ATIS	128.565	Rotterdam Info
TWR	118.205	Rotterdam Tower																		
	119.705	O/R																		
	122.180	Rotterdam Delivery Start-up control & clearance delivery																		
APP	122.990	Rotterdam Approach																		
ATIS	128.565	Rotterdam Info																		